

# **ISUZU UTE** **GENUINE OILS** **& LUBRICANTS**



***The Right Oils & Lubricants For Your Vehicle***

**DRIVING PEACE OF MIND**  
**ISUZUUTE.COM.AU**

**ISUZU**  
**UTE**  
GO YOUR OWN WAY

Isuzu UTE Genuine Oils & Lubricants are available exclusively from Isuzu UTE dealerships. Whether you have an Isuzu D-MAX or MU-X, all Isuzu UTE fluids are made to the same high-quality standard and meet the requirements to keep your D-MAX or MU-X powering through Australia's diverse conditions.

## GEAR OIL 75W-90

Engineered as a fully synthetic drivetrain lubricant to provide superior friction control, temperature stability and wear protection under all operating conditions.

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation.	Long gear and bearing life due to minimal deposits. Long seal life.
Outstanding protection against low speed/high torque wear and high speed scoring.	Increased load-carrying capability. Helps to reduce maintenance costs and long equipment life.
Exceptional shear stability.	Helps to retain viscosity and film strength under severe operating conditions to prevent wear.
Enhanced friction reduction properties.	Has potential for fuel economy and to reduce operating conditions.
Outstanding low temperature fluidity versus conventional oils.	Helps to reduce wear and increase ease of start-up.
Good resistance to foaming.	Helps to maintain film strength for reliable lubrication.
Compatible with typical automotive seals and gaskets.	Minimal leakage and reduced contamination.



Available in 1 Litre, 5 Litre and 20 Litre sizes.

## ENGINE OIL 15W-40

The lifeblood of the legendary Isuzu 3-litre turbo-diesel engine, this high performance diesel engine oil protects your engine from the moment you start, optimising performance, longevity and efficiency from your engine.

Features	Advantages and Potential Benefits
High thermal and oxidation stability.	Reduced sludge build-up, deposits and viscosity increase.
TBN reserves.	Deposit control and acid neutralisation.
Stay-in-grade shear stability.	Wear protection and viscosity control.
Advanced detergency/dispersancy.	Cleaner engines and longer component life.
Improved soot handling.	Improved viscosity control and used oil pumpability.
Excellent low temperature properties.	Start-up wear protection.
Component compatibility.	Longer gasket and seal life.
Meets demanding specifications of key OEMs.	One engine oil for mixed fleet operations.



Available in 1 Litre, 5 Litre and 20 Litre sizes.

## LONG LIFE COOLANT

Offers long-term cooling system with superior performance at higher operating temperatures.

Features	Advantages and Potential Benefits
Provides effective, long term corrosion protection for the six basic metal alloys; aluminium, brass, cast iron, steel, solder and copper – found in most heat transfer systems.	Superior performance at high operating temperatures.
Advanced formulation protects all cooling system metals against pitting, corrosion and erosion.	Reduces surface tension and provides better protection.
Nitrite, amine, phosphate, silicate (NAPS) free.	Biodegradable in its pure unused form.
Pre-diluted with demineralised water.	Ready to be poured directly into the cooling system as a complete service or top-up.



Available in 1 Litre, 5 Litre and 20 Litre sizes.

## AUTOMATIC TRANSMISSION FLUID

Formulated to provide optimum protection against wear in slip-controlled lock-up automatic transmissions, Isuzu Automatic Transmission Fluid (ATF) has been engineered specifically to meet the lubrication requirements of your Isuzu D-MAX or MU-X, with excellent viscosity stability, smoother gear shifts and maintaining performance and fuel economy.

Features	Advantages and Potential Benefits
High viscosity index.	Better protection during cold starts and high temperatures.
Excellent lubricating characteristics.	For quiet operation and smooth shifting in approved transmissions.
Controlled friction properties.	For smooth and efficient transmission of power across all normal temperature ranges.
Lubrication of transmissions in specified slip-controlled automatic transmissions.	Helps to control transmission shudder and provide excellent vehicle drivability.
Helps extend transmission life.	Excellent wear and control.
Long fluid life.	Based on outstanding oxidation resistance.
Excellent viscosity stability (high viscosity index) to help adequate lubrication.	Avoid excessive thinning in severe high-temperature service or thickening at low starting temperatures.
Resistance to foaming.	Greater stability and temperature control.
Superb protection against rusting and corrosion.	Extended service capability.
Compatibility with synthetic rubber seal materials.	Eliminates potential seal leaks.



Available in 1 Litre, 5 Litre and 20 Litre sizes.