

LDV is a division of SAIC Motor, which is a Fortune Global 500 company and the 7th largest automotive company in the world¹. SAIC Motor sells over 5 million vehicles annually and has joint ventures with Volkswagen and General Motors. In 2009 SAIC Motor acquired the commercial vehicles division of British Motor Corporation which included LDV.



	G10	G10+		
	DIESEL	PETROL	DIESEL	
	Manual	Automatic	Manual	Automatic
Engine	1.9 litre turbo diesel	2.0 TGI turbo charged petrol	2.0 D20 litre turbo diesel	2.0 D20 litre turbo diesel
Maximum Power (kW)	106	160	118	118
Maximum Torque (Nm)	350	330	375	375
Displacement (cc)	1850	1995	1996	1996
Transmission	Six speed manual	ZF eight speed automatic	Six speed manual	ZF eight speed automatic
Fuel Tank (Litres)	75	72	72	72
Fuel Consumption ² (Combined L/100km as per ADR 81/02)	8.3	11.1	8.2	8.2
Steering & Handling				
Hydraulic power assisted steering	✓	✓	✓	✓
Front suspension – Macpherson struts	✓	/	✓	✓
Rear suspension – five link coil springs	✓	-	-	-
Rear suspension – leaf springs	-	/	✓	✓
16" alloy wheels (6.5J x 16)	✓	✓	✓	✓
Tyres 215/70R16 LT	✓	√	✓	✓
Full size steel spare wheel	/	✓	✓	1
Brakes				
Front ventilated discs	✓	✓ ·	✓	/
Rear discs	✓	✓ /	✓	1
Anti Skid Brakes (ABS)	✓	/	✓	1
Electronic Brake Force Distribution (EBD)	✓	✓ /	✓	1
Electronic Stability Control (ESC)	✓		/	/
Emergency Brake Assist (EBA)	✓	✓	✓	✓
Interior Features				
Seats (2)	/	· /	/	/
Cruise control	-		-	/
Air conditioning	✓	/	√	/
Power windows (front)	✓		√	/
Audio system	✓	· /	√	/
Bluetooth for phone	✓		✓	/
Tilt adjustable steering wheel	√	· /	√	1
Apple CarPlay® / Smartphone connectivity	✓		/	/
7" multi-function display screen	✓	· /	√	/
Durable dark grey interior	✓	✓	√	✓
Exterior Features				
Dual side sliding doors	✓		√	/
Lift tail gate	✓	· /	√	1
Rear barn doors	0	-	0	0
Power side mirrors with integrated turning signal	✓		/	/

	G10	G10+		
	DIESEL	PETROL	DIESEL	
	Manual	Automatic	Manual	Automatic
Safety Features				•
Roll Movement Intervention (RMI)	✓	/	✓	1
Driver's and passenger airbags	✓	/	✓	1
Rear camera ³	✓	/	✓	/
Parking sensors ³	✓	/	✓	/
Remote keyless entry and central locking	✓	/	✓	/
Fog lamps rear	✓	/	✓	/
Tyre pressure monitoring system	/	/	√	1
Dimensions				
Length (mm)	5168	5168	5168	5168
Width (mm)	1980	1980	1980	1980
Height (mm)	1928	1928	1928	1928
Ground clearance (mm)	134	134	134	134
Wheel base (mm)	3198	3198	3198	3198
Turning circle diameter (m)	11.8	11.8	11.8	11.8
Cargo area length along floor (mm)	2500	2500	2500	2500
Cargo area width at widest point (mm)	1590	1590	1590	1590
Cargo area height (mm)	1270	1270	1270	1270
Wheel arch width (mm)	1278	1278	1278	1278
Rear door opening width at widest point (mm)	1370	1370	1370	1370
Rear door opening height (mm)	1179	1179	1179	1179
Side door opening width (mm)	820	820	820	820
Side door opening height (mm)	1165	1165	1165	1165
Gross combined mass ⁴	5000	4750	5000	5000
Gross vehicle mass (kg)	3000	3000	3000	3000
Tare weight (kg)	1970	1915	2005	2010
Payload (kg) ⁴	1030	1093	1015	1010
Front axle capacity (kg)	1370	1335	1335	1335
Rear axle capacity (kg)	1630	1665	1665	1665
Unbraked towing capacity (kg)	750	750	750	750
Braked towing capacity (kg)	1500	1000	1500	1500
Cargo volume (m³)	5.2	5.2	5.2	5.2
Warranty				
3 year/100,000km² Warranty & Roadside Assist ⁵	✓	✓ /	✓	✓
		_		

O = optional

- Fuel consumption figures according to ADR 81/02 derived from laboratory testing. Factors including but not limited to driving style, road and traffic conditions, environmental influences, vehicle condition and accessories fitted, will in practice in the real world lead to figures which generally differ from those advertised. Advertised figures are meant for comparison amongst vehicles only.
- 3. Safety technologies may not operate optimally under all driving conditions, operation and effectiveness depends on many factors. Driver is responsible for safe and attentive driving. Safety technologies are not a substitute for the the driver's control over the vehicle. See owner's manual for complete details.
- 4. Payload and tare weight figures are based on vehicle certification. It is the driver's responsibility to ensure: weight of fully loaded vehicles do not exceed GVM; front and rear axle load limits are not individually exceeded; the combined weight of the fully loaded vehicle (including tow ball download when towing) and trailer does not exceed the GCM; compliance to State and Territory towing regulations. Payload is the combined value of occupants, luggage, cargo, added options, accessories and tow ball download (when towing). Tare weight includes the vehicle with 10 litres of fuel and all standard equipment excluding occupants. Additional weights of optional features, occupants, luggage, cargo, accessories and tow ball download (when towing) must be taken into account when calculating payload and tare weight. When a genuine tow bar with wiring is fitted, and trailer is attached, parking sensors will be disabled.
- 5. Whichever occurs first.
- 6. Subject to terms, conditions and exclusions at Idvautomotive.com.au

All information in this document is correct at time of publication however variations may occur from time to time and Ateco Automotive Pty Ltd insofar as is permitted by law to do so, shall not be liable in any way as a result of any reliance by any person on anything contained in this document.

